



GDR201 - GDR201W

TUMBLE DRYERS
FROM SmallPRO RANGE



TUMBLE DRYERS GDR201 FROM SmallPRO RANGE

Characteristics

- Three levels of user-selectable temperatures. The working time can be freely set
- Three predetermined working cycles to facilitate the operator's choice
- Sensor of laundry residual moisture displayed through LED
- LED display showing the progress of the program and the time remaining at the end of cycle
- Top, front and side panels painted with gray powder
- Basket of galvanized sheet
- Ergonomic control panel
- Large dimensions of the port of loading / unloading opening up to 180° to facilitate the operations. The opening of the door can be reversed even once the appliance is installed
- Dust filter positioned in front and of a generous size for easy cleaning
- Powerful vacuum that ensures fast drying times and low operating costs

Options

- Heating available in electrical single-phase or three-phase



TUMBLE DRYERS GDR201W FROM SmallPRO RANGE

Characteristics

- Three levels of user-selectable temperatures. The working time can be freely set
- Three predetermined working cycles to facilitate the operator's choice
- Sensor of laundry residual moisture displayed through LED
- LED display showing the progress of the program and the time remaining at the end of cycle
- Top, front and side panels painted with white powder
- Basket of galvanized sheet
- Ergonomic control panel
- Large dimensions of the port of loading / unloading opening up to 180° to facilitate the operations. The opening of the door can be reversed even once the appliance is installed
- Dust filter positioned in front and of a generous size for easy cleaning
- Powerful vacuum that ensures fast drying times and low operating costs

Options

- Heating available in electrical single-phase, three-phase or single phase gas heated

Models GDR

		GDR201	GDR201W
Ratio capacity	1:20	9.9	9.9
Drum dimensions	Diameter (mm)	655	655
	Depth (mm)	550	550
	Volume (dm ³)	198	198
Door dimensions	Rounded shapes (mm)	530 x 425	530 x 425
Drum speed	rpm	50	50

Net dimensions and packing

		GDR201	GDR201W
Net dimensions	Width (mm)	683	683
	Depth (mm)	711	711
	Height (mm)	1027	1126
Packing dimensions	Width (mm)	737	737
	Depth (mm)	832	832
	Height (mm)	1276	1276
	Volume (m ³)	0.709	0.709
Net / Gross weight	kg	61 ÷ 66	61 ÷ 66

GAS models data

	V / ph / Hz	Version not available	
Power supply		-	230-240V 3~50Hz
		-	230-240V 1~50Hz
		-	380-415V 3N~50Hz
Thermal power	kW	-	5.3
Motor power	kW	-	0.25
Total electric power	kW	-	0.25
Fuse	A	-	10
Exhaust	Diameter (mm)	-	100
Noise	dB	-	<52

Electric models data

	V / ph / Hz	230-240V 3~50Hz	230-240V 3~50Hz
Power supply		230-240V 1~50Hz	230-240V 1~50Hz
		380-415V 3N~50Hz	380-415V 3N~50Hz
Thermal power	kW	5.35	5.35
Motor power	kW	0.25	0.25
Total electric power	kW	5.6	5.6
Fuse	A	15 ÷ 30	15 ÷ 30
Exhaust	Diameter (mm)	100	100
Noise	dB	<52	<52

grandimpianti i.l.e - Ali spa
via masiere, 211/c - 32037 sospiolo (BL) Italy
ph. +39 0437 848 711 - fax +39 0437 879 108
www.grandimpianti.com - info@grandimpianti.com



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =

an Ali Group Company



The Spirit of Excellence