



# EB10/15

TUMBLE DRYERS

## Drying in its essence

- Tumble dryers with stainless steel drum and skin-plate frame.
- Direct drive system instead of pulleys and drive belts.
- Automatic inversion of drum revolving direction by way of inverter.
- Drum speed automatically adjusted accordingly to the real laundry moisture.
- Exclusive system where the differential temperature control allows a significant savings in term of cycle length.
- Stainless steel filter on the exhaust channel.
- Standard equipped with G400 Dry electronic control with 35 drying cycles freely adjustable. 10 cycles already set.
- Stores and visualizes the alarmshistory. Operating parameters freely editable by the operator even during running cycle.
- Available on electric, gas or steam heating version with an average of 1kW each kg of laundry loaded.
- On request, available with vacuum power automatically adjusted accordingly to the real installation site and running conditions, humidity probe, different heating powers, Data track.



## Drying. Efficiently.

Grandimpianti I.L.E. has made drying a strength in the treatment process of laundry fabrics. Energy efficiency, only 1kW for each kg of laundry loaded, innovative control, drum made of steel, and compact dimensions, are a few of the solutions put in place to make the drying phase efficient.



## EBE Models

	10	15
Type of heating	electric	electric
Hourly output	12÷15	17÷20
Water evaporation l/h ca.	5÷7	7÷9
Ratio capacity (1/20)	10	15
Ratio capacity (1/25)	8	12
Drum size	width (mm) 761 depth (mm) 440 volume (dm <sup>3</sup> ) 200	width (mm) 761 depth (mm) 660 volume (dm <sup>3</sup> ) 300
Door size	mm 612	mm 612
Drum speed	rpm 2080	rpm 2080

### Net dimensions and packing

Dimensions	width (mm)	795	795
	depth (mm)	750	970
	height (mm)	1290	1290
Packing dimensions	width (mm)	850	850
	depth (mm)	810	1035
	height (mm)	1440	1440
Volume	m <sup>3</sup>	1	1.3
Net / Gross weight	kg	111/128	134/153

### Electric data

Electric supply	V/pH/Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
	V/pH/Hz	380-415V 3~50/60Hz	380-415V 3~50/60Hz
Heating power	V/pH/Hz	440-480V 3~60Hz	440-480V 3~60Hz
	kW	9.6	12
Motor power	kW	0.5	0.5
Total power	kW	10.1	12.5
Fuse	A	16-25	20-32
Noise	dB (A)	64	64

## EBG Models

Type of heating	gas	gas
Type of gas	G20 - G25 - G30 - G31	G20 - G25 - G30 - G31
Nominal thermal input	kW 16	kW 16
Motor power	kW 0.5	kW 0.5
Fuse	A 6	A 6

## EBV Models

Type of heating	steam	steam
Steam consumption	kg/h 30	kg/h 30
Steam pressure	kPa (bar) 400/600 (4/6)	kPa (bar) 400/600 (4/6)
Total power	kW 0.5	kW 0.5
Fuse	A 6	A 6

EB1015 201605 02 RIFGR00000000H007

The manufacturer declines all responsibility for any inaccuracies contained in this catalogue. The manufacturer reserves the right to bring, without warning, any modifications he might believe necessary without changing the essential characteristics of the product.

**grandimpianti i.l.e - Ali spa**  
via masiere, 211/c - 32037 sospiolo (BL) Italy  
ph. +39 0437 848 711 - fax +39 0437 879 108  
www.grandimpianti.com - info@grandimpianti.com



COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =  
= ISO 14001 =

an Ali Group Company



The Spirit of Excellence